



INPUT POWER (W) -CONTROL -**Clear Filters** Input Power Input **Operation Ambient** Power **THD Control** (W) Voltage **Factor** (%) **Temperature** 

Transformer MAX LOAD (W) -CONTROL -

**Clear Filters Control** Max Load (W) NON 20

NON 10 NON 75 95 ELV, NON 60

**Finishes** 

**Options** 

Mountings Mountings With A Power Supply

Copyright © B-K Lighting, Inc. | 40429 Brickyard Drive Madera, CA 93636 | MADE IN USA | +1 (559) 438-5800 | info@bklighting.com | bklighting.com This document contains proprietary information of B-K Lighting, inc. and its receipt or possession does not convey any rights to reproduce, disclose its contents, or to manufacture, use or sell anything it may describe. Technical information is subject to change at the discretion of B-K Lighting Inc. For the most current technical data, please refer to bklighting.com

Accesory

Input Voltage Power Factor THD (%) Operation Ambient Temperature Output Current Circuit Breaker Min Load (W)

LIGHT SOURCE -OPTIC -INPUT POWER (W) -CCT CRI -**Clear Filters** L70 L90B10 **IES** Current (mA) (Hours) (Hours) File **Drivers Output Voltage** InRush Output **Output Power** (Max-W) Current Current (Range)

Diagram

CONE

Dimming

Updated 05/26/2024

(Range)