



Light Source INPUT POWER (W) -OPTIC -LIGHT SOURCE -CCT CRI -**Clear Filters** Input Operating Light CCT **Delivered** MacAdam L70 **CBCP** Optic **CRI** Power Current (mA) Source Lumens (Lm) Ellipses (SDCM) (Hours) (Hours) (W)

Operation Ambient

Input Voltage Power Factor THD (%) Operation Ambient Temperature

Copyright © B-K Lighting, Inc. | 40429 Brickyard Drive Madera, CA 93636 | MADE IN USA | +1 (559) 438-5800 | info@bklighting.com | bklighting.com

Technical information is subject to change at the discretion of B-K Lighting Inc. For the most current technical data, please refer to bklighting.com

This document contains proprietary information of B-K Lighting, inc. and its receipt or possession does not convey any rights to reproduce, disclose its contents, or to

Temperature

InRush

Current

Output

Current

Output Power

(Max-W)

Drivers

CONTROL -

(W)

Transformer

CONTROL -

Clear Filters

Control

NON

NON

NON

ELV, NON 60

Finishes

Options

Accesory

Mountings

Mountings With A Power Supply

manufacture, use or sell anything it may describe.

Input Power Input

Max Load (W)

20

10

75

Clear Filters

Control

INPUT POWER (W) -

Voltage

MAX LOAD (W) -

Power

Factor

THD

(%)

95

L90B10 **IES** File

Diagram

CONE

Dimming

Updated 05/28/2024

(Range)

Output Voltage

Output Current Circuit Breaker Min Load (W)

(Range)