





L90B10

(Hours)

Output Voltage

(Range)

Output Current Circuit Breaker

L70

Output Power

(Max-W)

(Hours)

Diagram

CONE

Dimming

Min Load (W)

Updated 05/28/2024

(Range)

IES

File

Operating

Output

Current

Current (mA)

MacAdam

Ellipses (SDCM)

InRush

Current

LIGHTING							
Techn	ical						
Input voltage: 120-277V, 120V							
Light	Source						
LIGHTS	OURCE -	OF	PTIC -	ССТС	RI ▼	INPUT PO	יכ
Clear Filte Light Source	Optic	CCT (K)	CRI	Input Power (W)		ivered nens (Lm)	

ER (W) 🔻 BCP

INPUT POWER (W) -CONTROL -THD Input Power Input **Operation Ambient Power** (%) (W) Voltage **Temperature Factor**

Clear Filters Control Transformer

MAX LOAD (W) -

CONTROL -**Clear Filters** Max Load (W) Input Voltage **Power Factor** THD (%) Operation Ambient Temperature **Control** 20 10

NON 75 ELV, NON 60 95 Finishes

Mountings With A Power Supply

manufacture, use or sell anything it may describe.

Options

Accesory Mountings

NON

NON

Copyright © B-K Lighting, Inc. | 40429 Brickyard Drive Madera, CA 93636 | MADE IN USA | +1 (559) 438-5800 | info@bklighting.com | bklighting.com This document contains proprietary information of B-K Lighting, inc. and its receipt or possession does not convey any rights to reproduce, disclose its contents, or to

Technical information is subject to change at the discretion of B-K Lighting Inc. For the most current technical data, please refer to bklighting.com