





LIGHTING	
Technical	
Input voltage: 120-277V, 120V Light Source	
LIGHT SOURCE - OPTIC - CCT CRI - INPUT POWER (W) Clear Filters	

Input

Power

(W)

Power

Factor

CRI

INPUT POWER (W) -

Voltage

MAX LOAD (W) -

Input Voltage

Delivered

THD

(%)

Power Factor

95

Lumens (Lm)

CCT

Optic

Input Power Input

Max Load (W)

20

10

75

Light

Source

Drivers

CONTROL -

(W)

Transformer

CONTROL -

Clear Filters

Control

NON

NON

NON

ELV, NON 60

Finishes

Options

Accesory

Mountings

Mountings With A Power Supply

manufacture, use or sell anything it may describe.

Clear Filters

Control

CBCP

Operation Ambient

Copyright © B-K Lighting, Inc. | 40429 Brickyard Drive Madera, CA 93636 | MADE IN USA | +1 (559) 438-5800 | info@bklighting.com | bklighting.com

Technical information is subject to change at the discretion of B-K Lighting Inc. For the most current technical data, please refer to bklighting.com

This document contains proprietary information of B-K Lighting, inc. and its receipt or possession does not convey any rights to reproduce, disclose its contents, or to

Temperature

MacAdam

Ellipses (SDCM)

InRush

Current

THD (%) Operation Ambient Temperature

Operating

Output

Current

Current (mA)

L70

Output Power

(Max-W)

(Hours)

L90B10

(Hours)

Output Voltage

(Range)

Output Current Circuit Breaker

Diagram

CONE

Dimming

Min Load (W)

Updated 05/27/2024

(Range)

IES

File