



LIGHTING

Light Source

INPUT POWER (W) -

Operation Ambient

Power Factor THD (%) Operation Ambient Temperature

Copyright © B-K Lighting, Inc. | 40429 Brickyard Drive Madera, CA 93636 | MADE IN USA | +1 (559) 438-5800 | info@bklighting.com | bklighting.com

Technical information is subject to change at the discretion of B-K Lighting Inc. For the most current technical data, please refer to bklighting.com

This document contains proprietary information of B-K Lighting, inc. and its receipt or possession does not convey any rights to reproduce, disclose its contents, or to

Temperature

CBCP

MacAdam

Ellipses (SDCM)

InRush

Current

Operating

Output

Current

Current (mA)

L70

Output Power

(Max-W)

(Hours)

L90B10

(Hours)

Output Voltage

(Range)

Output Current Circuit Breaker

Diagram

CONE

Dimming

Min Load (W)

Updated 05/28/2024

(Range)

IES

File

OPTIC -

CRI

INPUT POWER (W) -

Voltage

MAX LOAD (W) -

Input Voltage

95

CCT

CCT CRI ▼

Delivered

THD

(%)

Lumens (Lm)

Input

Power

(W)

Power

Factor

LIGHT SOURCE -

Optic

Input Power Input

Max Load (W)

20

10

75

Clear Filters

Light

Source

Drivers

CONTROL -

(W)

Transformer

CONTROL -

Clear Filters

Control

NON

NON

NON

ELV, NON 60

Finishes

Options

Accesory

Mountings

Mountings With A Power Supply

manufacture, use or sell anything it may describe.

Clear Filters

Control