Project Type Date ARTI STAR - Tree Mount - Low Voltage Driver - LED High-Power - Aluminum - Cap A - 3 Fixtures @ 120° - Strap: 26" Min. To 32" Max. Tree Diameter

INPUT POWER (W) -

Operation Ambient

Power Factor THD (%) Operation Ambient Temperature

Temperature

CBCP

MacAdam

Ellipses (SDCM)

InRush

Current

Delivered

THD

(%)

95

Lumens (Lm)

Operating

Output

Current

Current (mA)





L90B10

(Hours)

Output Voltage

(Range)

Output Current Circuit Breaker

L70

Output Power

(Max-W)

(Hours)

Diagram

CONE

Dimming

Min Load (W)

Updated 05/26/2024

(Range)

IES

File

Technical Input voltage: 120V, 120-277V

LIGHT SOURCE -OPTIC -CCT CRI ▼

Light Source

Clear Filters Input

Light CCT Power Optic CRI Source (W)

Drivers

INPUT POWER (W) -CONTROL -**Clear Filters**

Input Power Input Power **Control** (W) Voltage **Factor**

Transformer MAX LOAD (W) -CONTROL -

Clear Filters Max Load (W) Input Voltage 20

10 75 ELV, NON 60

Finishes

Control

NON

NON

NON

Options

Accesory

Mountings With A Power Supply

manufacture, use or sell anything it may describe.

Mountings

Copyright © B-K Lighting, Inc. | 40429 Brickyard Drive Madera, CA 93636 | MADE IN USA | +1 (559) 438-5800 | info@bklighting.com | bklighting.com

Technical information is subject to change at the discretion of B-K Lighting Inc. For the most current technical data, please refer to bklighting.com

This document contains proprietary information of B-K Lighting, inc. and its receipt or possession does not convey any rights to reproduce, disclose its contents, or to