Project Type Date ARTI STAR - Tree Mount - Low Voltage Driver - LED High-Power - Aluminum - Cap A - 3 Fixtures @ 120° - Strap: 31" Min. To 38" Max. Tree Diameter

INPUT POWER (W) -

Operation Ambient

Power Factor THD (%) Operation Ambient Temperature

Temperature

CBCP

MacAdam

Ellipses (SDCM)

InRush

Current

Operating

Output

Current

Current (mA)



120V, 120-277V

CCT CRI ▼

Delivered

THD

(%)

Lumens (Lm)

Input



L90B10

(Hours)

Output Voltage

(Range)

Output Current Circuit Breaker

L70

Output Power

(Max-W)

(Hours)

Diagram

CONE

Dimming

Min Load (W)

Updated 05/28/2024

(Range)

IES

File

Lig	Light Source

Technical

Input voltage:

LIGHT SOURCE -OPTIC -

Clear Filters

Light Optic Source

CCT Power CRI (W)

Drivers

CONTROL -

INPUT POWER (W) -**Clear Filters**

Input Power Input **Power Control** (W) Voltage **Factor**

Transformer MAX LOAD (W) -CONTROL -

10 75 ELV, NON 60

Max Load (W)

20

Input Voltage

95

Finishes

Clear Filters

Control

NON

NON

NON

Options

Accesory

Mountings With A Power Supply

Mountings

manufacture, use or sell anything it may describe. Technical information is subject to change at the discretion of B-K Lighting Inc. For the most current technical data, please refer to bklighting.com

Copyright © B-K Lighting, Inc. | 40429 Brickyard Drive Madera, CA 93636 | MADE IN USA | +1 (559) 438-5800 | info@bklighting.com | bklighting.com

This document contains proprietary information of B-K Lighting, inc. and its receipt or possession does not convey any rights to reproduce, disclose its contents, or to