**Project** Type Date ARTI STAR - Tree Mount - Low Voltage Driver - LED High-Power - Aluminum - Cap A - 6 Fixtures @ 60° - Strap: 31" Min. To 38" Max. Tree Diameter

INPUT POWER (W) -

**Operation Ambient** 

Power Factor THD (%) Operation Ambient Temperature

**Temperature** 

**CBCP** 

MacAdam

Ellipses (SDCM)

InRush

Current

Operating

Output

Current

Current (mA)



120V, 120-277V

CCT CRI ▼

**Delivered** 

THD

(%)

95

Lumens (Lm)

Input

Power

**Factor** 



L90B10

(Hours)

**Output Voltage** 

(Range)

Output Current Circuit Breaker

L70

**Output Power** 

(Max-W)

(Hours)

Diagram

CONE

Dimming

Min Load (W)

Updated 05/27/2024

(Range)

**IES** 

File

**Light Source** 

**Control** 

**Clear Filters** 

NON

NON

NON

**Technical** 

Input voltage:

LIGHT SOURCE -OPTIC -**Clear Filters** 

Light CCT Optic Source

Power CRI (W)

**Drivers** 

(W)

CONTROL -INPUT POWER (W) -

**Clear Filters** 

Voltage

Input Power Input

Transformer MAX LOAD (W) -CONTROL -

Max Load (W) Input Voltage **Control** 20 10

ELV, NON 60

75

**Finishes** 

**Options** 

Accesory

Mountings

Mountings With A Power Supply

manufacture, use or sell anything it may describe.

Copyright © B-K Lighting, Inc. | 40429 Brickyard Drive Madera, CA 93636 | MADE IN USA | +1 (559) 438-5800 | info@bklighting.com | bklighting.com

Technical information is subject to change at the discretion of B-K Lighting Inc. For the most current technical data, please refer to bklighting.com

This document contains proprietary information of B-K Lighting, inc. and its receipt or possession does not convey any rights to reproduce, disclose its contents, or to