

Date

Project

Type



ARTI STAR - Tree Mount - Low Voltage Driver - LED High-Power - Aluminum - Cap B - 6 Fixtures @ 60° - Strap: 31" Min. To 38" Max. Tree Diameter



Technical

Input voltage: 120V, 120-277V

Light Source

LIGHT SOURCE OPTIC CCT CRI INPUT POWER (W)

Clear Filters

Light Source	Optic	CCT (K)	CRI	Input Power (W)	Delivered Lumens (Lm)	CBCP	MacAdam Ellipses (SDCM)	Operating Current (mA)	L70 (Hours)	L90B10 (Hours)	IES File	Diagram CONE
--------------	-------	---------	-----	-----------------	-----------------------	------	-------------------------	------------------------	-------------	----------------	----------	--------------

Drivers

CONTROL INPUT POWER (W)

Clear Filters

Control	Input Power (W)	Input Voltage	Power Factor	THD (%)	Operation Ambient Temperature	InRush Current	Output Current	Output Power (Max-W)	Output Voltage (Range)	Dimming (Range)
---------	-----------------	---------------	--------------	---------	-------------------------------	----------------	----------------	----------------------	------------------------	-----------------

Transformer

CONTROL MAX LOAD (W)

Clear Filters

Control	Max Load (W)	Input Voltage	Power Factor	THD (%)	Operation Ambient Temperature	Output Current	Circuit Breaker	Min Load (W)
NON	20							
NON	10							
NON	75							
ELV, NON	60			95				

Finishes

Options

Accessory

Mountings

Mountings With A Power Supply