Project Type Date ARTI STAR - Tree Mount - Low Voltage Driver - LED High-Power - Aluminum - Cap C - 2 Fixtures @ 180° - Strap: 21" Min. To 27" Max. Tree Diameter



120V, 120-277V

OPTIC -

CCT CRI ▼

Delivered

THD

(%)

Factor

Lumens (Lm)

Input

INPUT POWER (W) -

Operation Ambient

Power Factor THD (%) Operation Ambient Temperature

Temperature

CBCP

MacAdam

Ellipses (SDCM)

InRush

Current

Operating

Output

Current

Current (mA)



L90B10

(Hours)

Output Voltage

(Range)

Output Current Circuit Breaker

L70

Output Power

(Max-W)

(Hours)

Diagram

CONE

Dimming

Min Load (W)

Updated 05/28/2024

(Range)

IES

File

Light Source
LIGHT SOURCE -

Technical

Input voltage:

Clear Filters

Light CCT Optic Source

Power CRI (W)

Drivers

INPUT POWER (W) -

Voltage

MAX LOAD (W) -

Input Voltage

95

CONTROL -

Clear Filters Input Power Input **Power Control**

Max Load (W)

20

10

75

(W)

Transformer

CONTROL -**Clear Filters**

NON NON

Control

NON

ELV, NON 60

Finishes

Options

Accesory

Mountings

Mountings With A Power Supply

manufacture, use or sell anything it may describe.

This document contains proprietary information of B-K Lighting, inc. and its receipt or possession does not convey any rights to reproduce, disclose its contents, or to

Copyright © B-K Lighting, Inc. | 40429 Brickyard Drive Madera, CA 93636 | MADE IN USA | +1 (559) 438-5800 | info@bklighting.com | bklighting.com

Technical information is subject to change at the discretion of B-K Lighting Inc. For the most current technical data, please refer to bklighting.com