Project Type Date ARTI STAR - Wall Mount - Line Voltage Via Transformer - Lamp MR16 Gu5.3 - Aluminum -Surface Mount - Cap B - Height: 18"





Light Source

OPTIC -

CRI

Light Optic Source

Drivers

CONTROL -

(W)

Transformer

CONTROL -

Clear Filters

Control

NON

NON

NON

ELV, NON 60

Clear Filters

Control

Clear Filters

LIGHT SOURCE -

Technical

CCT

INPUT POWER (W) -Input Power Input Voltage

MAX LOAD (W) -

Max Load (W)

20

10

75

THD Power **Factor** (%)

95

CCT CRI -

Delivered

Lumens (Lm)

Input

Power

(W)

Operation Ambient Temperature

INPUT POWER (W) -

CBCP

InRush Current

This document contains proprietary information of B-K Lighting, inc. and its receipt or possession does not convey any rights to reproduce, disclose its contents, or to

Technical information is subject to change at the discretion of B-K Lighting Inc. For the most current technical data, please refer to bklighting.com

MacAdam

Ellipses (SDCM)

Input Voltage Power Factor THD (%) Operation Ambient Temperature

Output

Current

Operating

Current (mA)

L70

Output Power

(Max-W)

(Hours)

L90B10

(Hours)

Output Current Circuit Breaker Min Load (W)

Output Voltage

(Range)

Updated 05/28/2024

Diagram

CONE

Dimming

(Range)

IES

File

Finishes

Options Accesory

Mountings

Mountings With A Power Supply

manufacture, use or sell anything it may describe.

Copyright © B-K Lighting, Inc. | 40429 Brickyard Drive Madera, CA 93636 | MADE IN USA | +1 (559) 438-5800 | info@bklighting.com | bklighting.com