Project Type Date ARTI STAR - Wall Mount - Line Voltage Via Transformer - Lamp MR16 Gu5.3 - Aluminum -Surface Mount - Cap D - Height: 12"



INPUT POWER (W) -

Operation Ambient

Temperature

CBCP

MacAdam

Ellipses (SDCM)

InRush

Current

Operating

Output

Current

Current (mA)

L70

Output Power

(Max-W)

(Hours)

L90B10

(Hours)

Output Voltage

Output Current Circuit Breaker Min Load (W)

(Range)



Diagram

CONE

Dimming

Updated 05/27/2024

(Range)

IES

File

Light Source

CCT

OPTIC -

CRI

CCT CRI -

Delivered

THD

(%)

95

Lumens (Lm)

Input

Power

(W)

Source	Optic

Drivers

NON

NON

NON

Clear Filters

Light

LIGHT SOURCE -

Technical

INPUT POWER (W) -CONTROL -**Clear Filters**

Input Power Input Power Control (W) Voltage **Factor**

Transformer

MAX LOAD (W) -CONTROL -**Clear Filters Control** Max Load (W) Input Voltage Power Factor THD (%) Operation Ambient Temperature

20 10 75 ELV, NON 60

Finishes Options

Accesory

Mountings

Mountings With A Power Supply

manufacture, use or sell anything it may describe.

Copyright © B-K Lighting, Inc. | 40429 Brickyard Drive Madera, CA 93636 | MADE IN USA | +1 (559) 438-5800 | info@bklighting.com | bklighting.com

Technical information is subject to change at the discretion of B-K Lighting Inc. For the most current technical data, please refer to bklighting.com

This document contains proprietary information of B-K Lighting, inc. and its receipt or possession does not convey any rights to reproduce, disclose its contents, or to