Project Type Date ARTI STAR - Wall Mount - Low Voltage Driver - Lamp MR16 Gu5.3 - Aluminum - Surface Mount -Cap F - Height: 24" LIGHTING LIGHTING

INPUT POWER (W) -

Operation Ambient

Input Voltage Power Factor THD (%) Operation Ambient Temperature

Technical information is subject to change at the discretion of B-K Lighting Inc. For the most current technical data, please refer to bklighting.com

Temperature

CBCP

MacAdam

Ellipses (SDCM)

InRush

Current

Operating

Output

Current

Current (mA)

L70

Output Power

(Max-W)

(Hours)

L90B10

(Hours)

Output Voltage

Output Current Circuit Breaker Min Load (W)

(Range)

Delivered

THD

(%)

95

Lumens (Lm)



Diagram

CONE

Dimming

Updated 05/28/2024

(Range)

IES

File

LIGHT SOURCE -OPTIC -CCT CRI -**Clear Filters**

Optic

CCT

Dri	ive	rs	

CONTROL -

Light

Source

Technical

Light Source

INPUT POWER (W) -

Voltage

Input

Power

(W)

Power

Factor

CRI

Clear Filters Input Power Input Control (W)

Transformer MAX LOAD (W) -CONTROL -

Max Load (W)

20

10

Clear Filters Control NON

NON

NON 75 ELV, NON 60 **Finishes**

Options Accesory

Mountings Mountings With A Power Supply

Copyright © B-K Lighting, Inc. | 40429 Brickyard Drive Madera, CA 93636 | MADE IN USA | +1 (559) 438-5800 | info@bklighting.com | bklighting.com This document contains proprietary information of B-K Lighting, inc. and its receipt or possession does not convey any rights to reproduce, disclose its contents, or to manufacture, use or sell anything it may describe.