Project Type Date

ARTI STAR - Wall Mount - Remote Driver - LED COB - Aluminum - Surface Mount - Cap E - Height: 24"



120-277V, 120V



Diagram

CONE

Dimming

Updated 05/28/2024

(Range)

IES

File

Light Source

Input voltage:

Technical

LIGHT SOURCE -OPTIC -

Clear Filters

Optic

Light

Source (W)

Input Power Input

Voltage

Drivers

Power

Factor

CRI

THD

(%)

95

CCT CRI ▼

Delivered

Lumens (Lm)

Input

Power

Clear Filters

Control

(W)

CONTROL -INPUT POWER (W) -

MacAdam

Ellipses (SDCM)

InRush

Current

Operating

Output

Current

Current (mA)

L70

Output Power

(Max-W)

(Hours)

L90B10

(Hours)

Output Voltage

(Range)

INPUT POWER (W) -

CBCP

CONTROL -

Transformer

MAX LOAD (W) -**Clear Filters** Max Load (W) Input Voltage Power Factor THD (%) Operation Ambient Temperature Output Current Circuit Breaker Min Load (W) **Control**

Operation Ambient

Temperature

NON 75 ELV, NON 60

20

10

NON

NON

Finishes

Copyright © B-K Lighting, Inc. | 40429 Brickyard Drive Madera, CA 93636 | MADE IN USA | +1 (559) 438-5800 | info@bklighting.com | bklighting.com

This document contains proprietary information of B-K Lighting, inc. and its receipt or possession does not convey any rights to reproduce, disclose its contents, or to

Accesory

Mountings

Options

Technical information is subject to change at the discretion of B-K Lighting Inc. For the most current technical data, please refer to bklighting.com

manufacture, use or sell anything it may describe.

Mountings With A Power Supply