Project Type Date CAMINO STAR - Bollard - Low Voltage Driver - LED High-Power - Brass - Anchor Base - Style D -

Height: 18"



120V, 120-277V

OPTIC -

CRI

INPUT POWER (W) -

Voltage

MAX LOAD (W) -

Input Voltage

CCT CRI 🔻

Power

Power

Factor

Delivered

THD

Power Factor

(%)

Lumens (Lm)

INPUT POWER (W) -

Operation Ambient

Temperature

CBCP

MacAdam

Ellipses (SDCM)

InRush

Current

THD (%) Operation Ambient Temperature

This document contains proprietary information of B-K Lighting, inc. and its receipt or possession does not convey any rights to reproduce, disclose its contents, or to

Technical information is subject to change at the discretion of B-K Lighting Inc. For the most current technical data, please refer to bklighting.com

Operating

Output

Current

Current (mA)

L70

Output Power

Output Current

(Max-W)

(Hours)

L90B10

(Hours)

Output Voltage

Circuit Breaker

(Range)

Diagram

CONE

Dimming

Min Load (W)

Updated 05/28/2024

(Range)

IES

File



LIGHT SOURCE -

Light

Technical

Input voltage:

Light Source

Clear Filters Input

CCT

Optic Source

(W)

CONTROL -

Clear Filters Input Power Input **Control** (W)

Drivers

Transformer

CONTROL -

Clear Filters

Max Load (W) Control NON 20

10

NON

Finishes

Options

Accesory

Mountings

Mountings With A Power Supply

manufacture, use or sell anything it may describe.

Copyright © B-K Lighting, Inc. | 40429 Brickyard Drive Madera, CA 93636 | MADE IN USA | +1 (559) 438-5800 | info@bklighting.com | bklighting.com