**Project** Type Date

CENTAURI - Floodlight - Line Voltage Driver -Lamp Low Pressure Sodium - Aluminum - Knuckle Slipfitter - 4 Sided Shield - 55W





Diagram

CONE

Dimming

Min Load (W)

(Range)

**IES** 

File

LIGHT SOURCE -

**Clear Filters** 

Light

Source

**Technical** 

**Light Source** 

**Drivers** 

CONTROL -

(W)

Transformer

CONTROL -

Control Max Load (W)

**Clear Filters** 

**Finishes** 

**Options** 

Accesory

Mountings

Mountings With A Power Supply

manufacture, use or sell anything it may describe.

**Clear Filters** 

**Control** 

Input Power Input

CCT

Optic

INPUT POWER (W) -

Voltage

OPTIC -

**CRI** 

CCT CRI -

**Delivered** 

Lumens (Lm)

Input

Power

(W)

Power **Factor** MAX LOAD (W) -

Input Voltage

**Power Factor** 

**THD** 

(%)

INPUT POWER (W) -

**Operation Ambient** 

**Temperature** 

**CBCP** 

MacAdam

Ellipses (SDCM)

InRush

Current

Operating

Output

Current

Current (mA)

L70

**Output Power** 

Output Current

(Max-W)

(Hours)

L90B10

(Hours)

**Output Voltage** 

**Circuit Breaker** 

(Range)

Copyright © B-K Lighting, Inc. | 40429 Brickyard Drive Madera, CA 93636 | MADE IN USA | +1 (559) 438-5800 | info@bklighting.com | bklighting.com

Technical information is subject to change at the discretion of B-K Lighting Inc. For the most current technical data, please refer to bklighting.com

This document contains proprietary information of B-K Lighting, inc. and its receipt or possession does not convey any rights to reproduce, disclose its contents, or to

THD (%) Operation Ambient Temperature

Updated 05/26/2024