Project Type Date

CENTAURI - Floodlight - Line Voltage Driver -Lamp Low Pressure Sodium - Aluminum - Knuckle Slipfitter - No Shield - 90W





Diagram

CONE

Dimming

Min Load (W)

Updated 05/27/2024

(Range)

IES

File

LIGHT SOURCE -

Clear Filters

Light

Light Source

Technical

Optic Source

Drivers

(W)

Transformer

CONTROL -

Control Max Load (W)

Clear Filters

Finishes

Options

Accesory

Mountings

Mountings With A Power Supply

manufacture, use or sell anything it may describe.

CONTROL -

Clear Filters

Control

INPUT POWER (W) -Input Power Input Voltage

CCT

OPTIC -

CRI

CCT CRI -

Delivered

Lumens (Lm)

Input

Power

(W)

Power **Factor**

MAX LOAD (W) -

Input Voltage **Power Factor**

THD

(%)

INPUT POWER (W) -

Operation Ambient

Temperature

CBCP

MacAdam

Ellipses (SDCM)

InRush

THD (%) Operation Ambient Temperature

Current

Operating

Output

Current

Current (mA)

L70

Output Power

Output Current

(Max-W)

(Hours)

L90B10

(Hours)

Output Voltage

Circuit Breaker

(Range)

Copyright © B-K Lighting, Inc. | 40429 Brickyard Drive Madera, CA 93636 | MADE IN USA | +1 (559) 438-5800 | info@bklighting.com | bklighting.com

This document contains proprietary information of B-K Lighting, inc. and its receipt or possession does not convey any rights to reproduce, disclose its contents, or to

Technical information is subject to change at the discretion of B-K Lighting Inc. For the most current technical data, please refer to bklighting.com