

DENALI - Tree Mount - Line Voltage Driver - LED COB - Aluminum - Cap C - 2 Fixtures @ 180° - Strap: 31" Min. To 38" Max. Tree Diameter



Technical

CCT(K):	2700, 3000, 4000, 3500
CRI:	Ra > 80, R9 > 15, Ra > 90, R9 > 50, Ra > 80, R9 >15
Input voltage:	120-277V, 120V

Light Source

Clear Filters

Light Source	Optic	CCT (K)	CRI	Input Power (W)	Delivered Lumens (Lm)	CBCP	MacAdam Ellipses (SDCM)	Operating Current (mA)	L70 (Hours)	L90B10 (Hours)	IES File	Diagram CONE
--------------	-------	---------	-----	-----------------	-----------------------	------	-------------------------	------------------------	-------------	----------------	----------	--------------

Drivers

Clear Filters

Control	Input Power (W)	Input Voltage	Power Factor	THD (%)	Operation Ambient Temperature	InRush Current	Output Current	Output Power (Max-W)	Output Voltage (Range)	Dimming (Range)
---------	-----------------	---------------	--------------	---------	-------------------------------	----------------	----------------	----------------------	------------------------	-----------------

Transformer

Clear Filters

Control	Max Load (W)	Input Voltage	Power Factor	THD (%)	Operation Ambient Temperature	Output Current	Circuit Breaker	Min Load (W)
---------	--------------	---------------	--------------	---------	-------------------------------	----------------	-----------------	--------------

Finishes

Options

Accessory

Mountings

Mountings With A Power Supply