
**Project** Type Date GOLD STAR - In-Grade - Low Voltage Driver - LED High-Power - Stainless Steel - Round - Faceplate Surface Mount



120V, 120-277V

CCT CRI ▼

**Delivered** 

THD

(%)

95

95

Lumens (Lm)

INPUT POWER (W) -

**Operation Ambient** 

Power Factor THD (%) Operation Ambient Temperature

**Temperature** 

**CBCP** 

MacAdam

Ellipses (SDCM)

InRush

Current

Operating

Output

Current

Current (mA)

L70

**Output Power** 

(Max-W)

(Hours)

L90B10

(Hours)

**Output Voltage** 

(Range)

Output Current Circuit Breaker



Diagram

CONE

Dimming

Min Load (W)

Updated 05/26/2024

(Range)

**IES** 

File

## **Light Source**

**Technical** 

Input voltage:

OPTIC -LIGHT SOURCE -**Clear Filters** 

Light Optic

Input CCT Power CRI Source (W)

**Drivers** 

CONTROL -

**Clear Filters Control** 

Input Power Input Power (W) Voltage **Factor** 

INPUT POWER (W) -

CONTROL -

**Control** 

NON

NON

NON

Transformer

MAX LOAD (W) -**Clear Filters** 

Max Load (W) Input Voltage 20 10 ELV, NON 60

**Finishes** 

75

Accesory Mountings

**Options** 

Copyright © B-K Lighting, Inc. | 40429 Brickyard Drive Madera, CA 93636 | MADE IN USA | +1 (559) 438-5800 | info@bklighting.com | bklighting.com

Mountings With A Power Supply

manufacture, use or sell anything it may describe.

This document contains proprietary information of B-K Lighting, inc. and its receipt or possession does not convey any rights to reproduce, disclose its contents, or to

Technical information is subject to change at the discretion of B-K Lighting Inc. For the most current technical data, please refer to bklighting.com