Date	Project	Туре	

HUME - Pole Top - Line Voltage Driver - LED COB -Aluminum - Round - Rear Knuckle - Cap C - Single





Technical

Input voltage: 120-277V, 120V

Light Source

LIGHT SC Clear Filter		OP		CCT CR		OWER (W)						
Light Source	Optic	ССТ (К)	CRI	Input Power (W)	Delivered Lumens (Lm)	CBCP	MacAdam Ellipses (SDCM)	Operating Current (mA)	L70 (Hours)	L90B10 (Hours)	IES File	Diagram CONE

Drivers

CONT	ROL –	NPUT POWE	R (W) 🔻							
Clear Filt	ters									
Control	Input Power (W)	Input Voltage	Power Factor	THD (%)	Operation Ambient Temperature	InRush Current	Output Current	Output Power (Max-W)	Output Voltage (Range)	Dimming (Range)

Transformer

	MAX LOAD (W) 👻
Clear Filters	

Finishes

Options			
Accesory			
Mountings			

Mountings With A Power Supply

Copyright © B-K Lighting, Inc. | 40429 Brickyard Drive Madera, CA 93636 | MADE IN USA | +1 (559) 438-5800 | info@bklighting.com | bklighting.com

This document contains proprietary information of B-K Lighting, inc. and its receipt or possession does not convey any rights to reproduce, disclose its contents, or to manufacture, use or sell anything it may describe.

Technical information is subject to change at the discretion of B-K Lighting Inc. For the most current technical data, please refer to bklighting.com

Updated 05/26/2024