

MINI MICRO - Floodlight - Low Voltage Driver - LED High-Power - Brass - Threaded Knuckle Mount - Cap E



Technical

CCT(K): 2700, 3000, 4000, 1500, 3500
CRI: Ra > 80, R9 > 15, -, Ra > 90, R9 > 50, Ra > 80, R9 > 15
Lens: Soft Focus, Rectilinear
Shielding: Not included (Standard), Honeycomb Baffle
Wiring length: 5 Ft Leads, 25 Ft Lead
Input voltage: 120V, 120-277V

Light Source

LIGHT SOURCE ▾ **OPTIC** ▾ **CCT CRI** ▾ **INPUT POWER (W)** ▾

Clear Filters

Light Source	Optic	CCT (K)	CRI	Input Power (W)	Delivered Lumens (Lm)	CBCP	MacAdam Ellipse (SDCM)	Operating Current (mA)	L70 (Hours)	L90B10 (Hours)	IES File	Diagram CONE
e72	Spot (°)	4000	Ra > 80, R9 > 15				2					
e72	Spot (°)	4000	Ra > 80, R9 > 15				2					
e73	Asymmetrical (°)	1500	-				2					
e73	Narrow Flood (°)	1500	-				2					
e73	Spot (°)	1500	-				2					
e73	Spot (°)	1500	-				2					
e85	Narrow Flood (°)	2700	Ra > 90, R9 > 50				2					
e85	Spot (°)	2700	Ra > 90, R9 > 50				2					
e85	Spot (°)	2700	Ra > 90, R9 > 50				2					
e86	Asymmetrical (°)	3000	Ra > 90, R9 > 50				2					
e86	Spot (°)	3000	Ra > 90, R9 > 50				2					
e86	Spot (°)	3000	Ra > 90, R9 > 50				2					
e87	Asymmetrical (°)	3500	Ra > 80, R9 > 15				2					
e87	Narrow Flood (°)	3500	Ra > 80, R9 > 15				2					
e87	Spot (°)	3500	Ra > 80, R9 > 15				2					
e87	Spot (°)	3500	Ra > 80, R9 > 15				2					
e70	Asymmetrical (°)	2700	Ra > 80, R9 > 15				2					
e70	Narrow Flood (°)	2700	Ra > 80, R9 > 15				2					
e70	Spot (°)	2700	Ra > 80, R9 > 15				2					
e71	Asymmetrical (°)	3000	Ra > 80, R9 > 15				2					
e72	Asymmetrical (°)	4000	Ra > 80, R9 > 15				2					
e72	Narrow Flood (°)	4000	Ra > 80, R9 > 15				2					

Drivers

CONTROL ▾ **INPUT POWER (W)** ▾

Clear Filters

Control	Input Power (W)	Input Voltage	Power Factor	THD (%)	Operation Ambient Temperature	InRush Current	Output Current	Output Power (Max-W)	Output Voltage (Range)	Dimming (Range)
---------	-----------------	---------------	--------------	---------	-------------------------------	----------------	----------------	----------------------	------------------------	-----------------

Transformer

CONTROL ▾ **MAX LOAD (W)** ▾

Clear Filters

Control	Max Load (W)	Input Voltage	Power Factor	THD (%)	Operation Ambient Temperature	Output Current	Circuit Breaker	Min Load (W)
---------	--------------	---------------	--------------	---------	-------------------------------	----------------	-----------------	--------------

NON 20

NON 10

Finishes

STANDARD FINISHES



RAL COLORS



Options

Accessory

Mountings

Mountings With A Power Supply