Project Type Date NITE STAR - Ceiling Mount - Low Voltage Driver - Lamp MR16 Gu5.3 - Aluminum - Round - Pendant Mount - Cap E

INPUT POWER (W) -

Operation Ambient

Temperature

CBCP

MacAdam

Ellipses (SDCM)

InRush

Current

Operating

Output

Current

Current (mA)

L70

Output Power

(Max-W)

(Hours)

L90B10

(Hours)

Output Voltage

Output Current Circuit Breaker Min Load (W)

(Range)





Diagram

CONE

Dimming

Updated 05/28/2024

(Range)

IES

File

LIGHT SOURCE -**Clear Filters**

Light

Source

Technical

Light Source

CONTROL -

(W)

Transformer

CONTROL -

Max Load (W)

20

10

60

75

Clear Filters

Control

NON

NON

NON

ELV, NON

Finishes

Options

Accesory

Mountings

Clear Filters

Control

Drivers

CCT

Optic

INPUT POWER (W) -Input Power Input Voltage

OPTIC -

CRI

CCT CRI -

Delivered

Lumens (Lm)

Input

Power

(W)

Power **Factor** MAX LOAD (W) -

Input Voltage Power Factor THD (%) Operation Ambient Temperature 95 95

THD

(%)

This document contains proprietary information of B-K Lighting, inc. and its receipt or possession does not convey any rights to reproduce, disclose its contents, or to manufacture, use or sell anything it may describe. Technical information is subject to change at the discretion of B-K Lighting Inc. For the most current technical data, please refer to bklighting.com

Mountings With A Power Supply

Copyright © B-K Lighting, Inc. | 40429 Brickyard Drive Madera, CA 93636 | MADE IN USA | +1 (559) 438-5800 | info@bklighting.com | bklighting.com