NITE STAR - Tree Mount - Low Voltage Driver - LED High-Power - Aluminum - Round - Cap B - 6 Fixtures @ 60° - Strap: 31" Min. To 38" Max. Tree



120V, 120-277V

Technical

Input voltage:

Mountings

Mountings With A Power Supply

manufacture, use or sell anything it may describe.

Diameter



Light Source												
LIGHTSO	OURCE •	ОРТІ	c 🔻 Cc	TCRI 🔻	INPUT POWE	R (W) -						
Clear Filter	′s											
Light Source	Optic	CCT (K)	Input CRI Powe (W)	r Deliv	rered ens (Lm)	H(:D	cAdam oses (SDCM)	Operating Current (mA)	L70 (Hours)		IES File	Diagram CONE
Drivers	;											
CONTRO	DL 🔻	INPUT PO	WER (W) 🔻									
	rs nput Powe W)	r Input Voltage	Power Factor	THD (%)	Operation Am Temperature	nbient	InRush Current	Output Current	Output Power (Max-W)	Output Volto (Range)	age	Dimming (Range)
Transfo	DL 🔻	MAX LOAE	D (W) ~									
Clear Filters Control	Max Loc	ad (W) Ir	nput Voltage	Power Fac	ctor THD (%)) Operati	on Ambient Te	emperature	Output Current	Circuit Bred	aker	Min Load (W)
NON	20											
NON	10											
ELV, NON	60			95								
NON	75			95								
Finishe	es											
Option	S											
Acceso	ory											

Copyright © B-K Lighting, Inc. | 40429 Brickyard Drive Madera, CA 93636 | MADE IN USA | +1 (559) 438-5800 | info@bklighting.com | bklighting.com

Technical information is subject to change at the discretion of B-K Lighting Inc. For the most current technical data, please refer to bklighting.com

This document contains proprietary information of B-K Lighting, inc. and its receipt or possession does not convey any rights to reproduce, disclose its contents, or to

Updated 05/26/2024