**Project** Type Date NITE STAR - Wall Mount - Low Voltage Driver - LED High-Power - Brass - Round - Canopy BC6 - Cap C - Dual - Downlight And Uplight



120V, 120-277V

OPTIC -

CCT CRI ▼

**Delivered** 

THD

(%)

95

95

Lumens (Lm)

INPUT POWER (W) -

**Operation Ambient** 

Power Factor THD (%) Operation Ambient Temperature

**Temperature** 

**CBCP** 

MacAdam

Ellipses (SDCM)

InRush

Current

Operating

Output

Current

Current (mA)

L70

**Output Power** 

(Max-W)

(Hours)

L90B10

(Hours)

**Output Voltage** 

(Range)

Output Current Circuit Breaker



Diagram

CONE

Dimming

Min Load (W)

Updated 05/28/2024

(Range)

**IES** 

File

LIGHT SOURCE -

Technical

Input voltage:

**Light Source** 

**Clear Filters** Input

Light CCT Power Optic CRI Source (W)

**Drivers** 

INPUT POWER (W) -CONTROL -**Clear Filters** 

Input Power Input Power **Control** Voltage (W) **Factor** 

Transformer

MAX LOAD (W) -

**Clear Filters** Max Load (W) Input Voltage **Control** NON 20 NON 10

60

NON 75

ELV, NON

CONTROL -

**Finishes** 

Accesory

Mountings

Mountings With A Power Supply

manufacture, use or sell anything it may describe.

**Options** 

Copyright © B-K Lighting, Inc. | 40429 Brickyard Drive Madera, CA 93636 | MADE IN USA | +1 (559) 438-5800 | info@bklighting.com | bklighting.com

This document contains proprietary information of B-K Lighting, inc. and its receipt or possession does not convey any rights to reproduce, disclose its contents, or to

Technical information is subject to change at the discretion of B-K Lighting Inc. For the most current technical data, please refer to bklighting.com