

# STEP STAR - Bollard - Line Voltage Via Transformer - Lamp MR16 Gu5.3 - Aluminum - Round - Anchor Base - Faceplate: Standard - Pattern B - Height: 18"



## Technical

### Light Source

Clear Filters

| Light Source | Optic | CCT (K) | CRI              | Input Power (W) | Delivered Lumens (Lm) | CBCP | MacAdam Ellipses (SDCM) | Operating Current (mA) | L70 (Hours) | L90B10 (Hours) | IES File | Diagram CONE |
|--------------|-------|---------|------------------|-----------------|-----------------------|------|-------------------------|------------------------|-------------|----------------|----------|--------------|
|              | (°)   | 2700    | Ra > 80, R9 > 15 |                 |                       |      | 2                       |                        |             |                |          |              |
|              | (°)   | 3000    | Ra > 80, R9 > 15 |                 |                       |      | 2                       |                        |             |                |          |              |
|              | (°)   | 4000    | Ra > 80, R9 > 15 |                 |                       |      | 2                       |                        |             |                |          |              |
|              | (°)   | 1500    | -                |                 |                       |      | 2                       |                        |             |                |          |              |
|              | (°)   | 2700    | Ra > 90, R9 > 50 |                 |                       |      | 2                       |                        |             |                |          |              |
|              | (°)   | 3000    | Ra > 90, R9 > 50 |                 |                       |      | 2                       |                        |             |                |          |              |
|              | (°)   | 3500    | Ra > 80, R9 > 15 |                 |                       |      | 2                       |                        |             |                |          |              |

### Drivers

Clear Filters

| Control | Input Power (W) | Input Voltage | Power Factor | THD (%) | Operation Ambient Temperature | InRush Current | Output Current | Output Power (Max-W) | Output Voltage (Range) | Dimming (Range) |
|---------|-----------------|---------------|--------------|---------|-------------------------------|----------------|----------------|----------------------|------------------------|-----------------|
|---------|-----------------|---------------|--------------|---------|-------------------------------|----------------|----------------|----------------------|------------------------|-----------------|

### Transformer

Clear Filters

| Control  | Max Load (W) | Input Voltage | Power Factor | THD (%) | Operation Ambient Temperature | Output Current | Circuit Breaker | Min Load (W) |
|----------|--------------|---------------|--------------|---------|-------------------------------|----------------|-----------------|--------------|
| NON      | 20           |               |              |         |                               |                |                 |              |
| NON      | 10           |               |              |         |                               |                |                 |              |
| ELV, NON | 60           |               | 95           |         |                               |                |                 |              |
| NON      | 75           |               | 95           |         |                               |                |                 |              |

### Finishes

### Options

### Accessory

### Mountings

### Mountings With A Power Supply