

# STEP STAR - Wall Recessed - Low Voltage Driver - LED High-Power - Aluminum - Square - Junction Box - Faceplate: Visor



## Technical

Input voltage: 120V, 120-277V

## Light Source

Clear Filters

| Light Source | Optic | CCT (K) | CRI              | Input Power (W) | Delivered Lumens (Lm) | CBCP | MacAdam Ellipses (SDCM) | Operating Current (mA) | L70 (Hours) | L90B10 (Hours) | IES File | Diagram CONE |
|--------------|-------|---------|------------------|-----------------|-----------------------|------|-------------------------|------------------------|-------------|----------------|----------|--------------|
|              | (°)   | 2700    | Ra > 80, R9 > 15 |                 |                       |      | 2                       |                        |             |                |          |              |
|              | (°)   | 3000    | Ra > 80, R9 > 15 |                 |                       |      | 2                       |                        |             |                |          |              |
|              | (°)   | 4000    | Ra > 80, R9 > 15 |                 |                       |      | 2                       |                        |             |                |          |              |
|              | (°)   | 1500    | -                |                 |                       |      | 2                       |                        |             |                |          |              |
|              | (°)   | 2700    | Ra > 90, R9 > 50 |                 |                       |      | 2                       |                        |             |                |          |              |
|              | (°)   | 3000    | Ra > 90, R9 > 50 |                 |                       |      | 2                       |                        |             |                |          |              |
|              | (°)   | 3500    | Ra > 80, R9 > 15 |                 |                       |      | 2                       |                        |             |                |          |              |

## Drivers

Clear Filters

| Control | Input Power (W) | Input Voltage | Power Factor | THD (%) | Operation Ambient Temperature | InRush Current | Output Current | Output Power (Max-W) | Output Voltage (Range) | Dimming (Range) |
|---------|-----------------|---------------|--------------|---------|-------------------------------|----------------|----------------|----------------------|------------------------|-----------------|
|         |                 |               |              |         |                               |                |                |                      |                        |                 |

## Transformer

Clear Filters

| Control  | Max Load (W) | Input Voltage | Power Factor | THD (%) | Operation Ambient Temperature | Output Current | Circuit Breaker | Min Load (W) |
|----------|--------------|---------------|--------------|---------|-------------------------------|----------------|-----------------|--------------|
| NON      | 20           |               |              |         |                               |                |                 |              |
| NON      | 10           |               |              |         |                               |                |                 |              |
| ELV, NON | 60           |               | 95           |         |                               |                |                 |              |
| NON      | 75           |               | 95           |         |                               |                |                 |              |

## Finishes

## Options

## Accessory

## Mountings

## Mountings With A Power Supply