


STEP STAR - Wall Recessed - Low Voltage Driver - LED High-Power - Stainless Steel - Round - Core Drill - Faceplate: Standard - Pattern B - Mini



Technical

Input voltage: 120V, 120-277V

Light Source

LIGHT SOURCE ▾ **OPTIC** ▾ **CCT CRI** ▾ **INPUT POWER (W)** ▾

Clear Filters

Light Source	Optic	CCT (K)	CRI	Input Power (W)	Delivered Lumens (Lm)	CBCP	MacAdam Ellipses (SDCM)	Operating Current (mA)	L70 (Hours)	L90B10 (Hours)	IES File	Diagram CONE
	(°)	2700	Ra > 80, R9 > 15				2					
	(°)	3000	Ra > 80, R9 > 15				2					
	(°)	4000	Ra > 80, R9 > 15				2					
	(°)	1500	-				2					
	(°)	2700	Ra > 90, R9 > 50				2					
	(°)	3000	Ra > 90, R9 > 50				2					
	(°)	3500	Ra > 80, R9 > 15				2					

Drivers

CONTROL ▾ **INPUT POWER (W)** ▾

Clear Filters

Control	Input Power (W)	Input Voltage	Power Factor	THD (%)	Operation Ambient Temperature	InRush Current	Output Current	Output Power (Max-W)	Output Voltage (Range)	Dimming (Range)

Transformer

CONTROL ▾ **MAX LOAD (W)** ▾

Clear Filters

Control	Max Load (W)	Input Voltage	Power Factor	THD (%)	Operation Ambient Temperature	Output Current	Circuit Breaker	Min Load (W)
NON	20							
NON	10							
ELV, NON	60		95					
NON	75		95					

Finishes

Options

Accessory

Mountings

Mountings With A Power Supply