

Date

Project

Type



YUKON - Wall Recessed - Line Voltage Driver - LED High-Power - Aluminum - Rectangular Vertical - Junction Box - Faceplate: Deco - Direct - Wide Throw



Technical

Input voltage: 120V, 120-277V

Light Source

LIGHT SOURCE OPTIC CCT CRI INPUT POWER (W)

Clear Filters

| Light Source | Optic | CCT (K) | CRI | Input Power (W) | Delivered Lumens (Lm) | CBCP | MacAdam Ellipses (SDCM) | Operating Current (mA) | L70 (Hours) | L90B10 (Hours) | IES File | Diagram CONE |
|--------------|-------|---------|------------------|-----------------|-----------------------|------|-------------------------|------------------------|-------------|----------------|----------|--------------|
| | (°) | 2700 | Ra > 80, R9 > 15 | | | | 2 | | | | | |
| | (°) | 2700 | Ra > 90, R9 > 50 | | | | 2 | | | | | |
| | (°) | 3000 | Ra > 80, R9 > 15 | | | | 2 | | | | | |
| | (°) | 3000 | Ra > 90, R9 > 50 | | | | 2 | | | | | |
| | (°) | 3500 | Ra > 80, R9 > 15 | | | | 2 | | | | | |
| | (°) | 3500 | Ra > 90, R9 > 50 | | | | 2 | | | | | |
| | (°) | 4000 | Ra > 80, R9 > 15 | | | | 2 | | | | | |
| | (°) | 4000 | Ra > 90, R9 > 50 | | | | 2 | | | | | |
| | (°) | 2700 | Ra > 80, R9 > 15 | | | | 2 | | | | | |
| | (°) | 2700 | Ra > 90, R9 > 50 | | | | 2 | | | | | |
| | (°) | 3000 | Ra > 80, R9 > 15 | | | | 2 | | | | | |
| | (°) | 3000 | Ra > 90, R9 > 50 | | | | 2 | | | | | |
| | (°) | 3500 | Ra > 80, R9 > 15 | | | | 2 | | | | | |
| | (°) | 3500 | Ra > 90, R9 > 50 | | | | 2 | | | | | |
| | (°) | 4000 | Ra > 80, R9 > 15 | | | | 2 | | | | | |
| | (°) | 4000 | Ra > 90, R9 > 50 | | | | 2 | | | | | |

Drivers

CONTROL INPUT POWER (W)

Clear Filters

| Control | Input Power (W) | Input Voltage | Power Factor | THD (%) | Operation Ambient Temperature | InRush Current | Output Current | Output Power (Max-W) | Output Voltage (Range) | Dimming (Range) |
|---------|-----------------|---------------|--------------|---------|-------------------------------|----------------|----------------|----------------------|------------------------|-----------------|
|---------|-----------------|---------------|--------------|---------|-------------------------------|----------------|----------------|----------------------|------------------------|-----------------|

Transformer

CONTROL MAX LOAD (W)

Clear Filters

| Control | Max Load (W) | Input Voltage | Power Factor | THD (%) | Operation Ambient Temperature | Output Current | Circuit Breaker | Min Load (W) |
|---------|--------------|---------------|--------------|---------|-------------------------------|----------------|-----------------|--------------|
|---------|--------------|---------------|--------------|---------|-------------------------------|----------------|-----------------|--------------|

Finishes

Options

Accessory

Mountings

Mountings With A Power Supply