Project Type Date ALPINE - Wall Mount - Line Voltage Driver - Lamp PAR30 - Aluminum - Surface Mount - Cap C - Dual - Downlight And Uplight LIGHTING LIGHTING

Technical Delivered Lumens:

INPUT POWER (W) -

Operation Ambient

Copyright © B-K Lighting, Inc. | 40429 Brickyard Drive Madera, CA 93636 | MADE IN USA | +1 (559) 438-5800 | info@bklighting.com | bklighting.com

Technical information is subject to change at the discretion of B-K Lighting Inc. For the most current technical data, please refer to bklighting.com

This document contains proprietary information of B-K Lighting, inc. and its receipt or possession does not convey any rights to reproduce, disclose its contents, or to

Temperature

CBCP

MacAdam

Ellipses (SDCM)

InRush

Current

THD (%) Operation Ambient Temperature

Operating

Output

Current

Current (mA)

L70

Output Power

Output Current

(Max-W)

(Hours)

L90B10

(Hours)

Output Voltage

Circuit Breaker

(Range)

Diagram

CONE

Dimming

Min Load (W)

Updated 05/30/2024

(Range)

IES

File

OPTIC -

CRI

INPUT POWER (W) -

Voltage

MAX LOAD (W) -

Input Voltage

CCT

CCT CRI ▼

Delivered

THD

Power Factor

(%)

Lumens (Lm)

Input

Power

(W)

Power

Factor

LIGHT SOURCE -

Optic

Input Power Input

Clear Filters

Light

Source

Drivers

CONTROL -

(W)

Transformer

CONTROL -

Control Max Load (W)

Clear Filters

Finishes

Options

Accesory

Mountings

Mountings With A Power Supply

manufacture, use or sell anything it may describe.

Clear Filters

Control

Light Source