

ARTI STAR - Floodlight - Line Voltage Driver - LED COB - Aluminum - Pipe P11 - 18" Junction Box - Cap D - Height: 24"



Technical

Delivered Lumens: -

Control: Non Dimming, ELV Dimming (For use with Electronic Low Voltage Dimmer), INC Dimming (For use with Incandescent Dimmer), 0-10V

Lens: Clear (Standard), Soft Focus, Rectilinear

Shielding: Not included (Standard), Honeycomb Baffle

Input voltage: 120V, 120-277V

Light Source

Clear Filters

Light Source	Optic	CCT (K)	CRI	Input Power (W)	Delivered Lumens (Lm)	CBCP	MacAdam Ellipses (SDCM)	Operating Current (mA)	L70 (Hours)	L90B10 (Hours)	IES File	Diagram CONE
Flood (°)		2700	Ra > 80, R9 > 15				2					
Spot (°)		2700	Ra > 80, R9 > 15				2					
Wide Flood (°)		2700	Ra > 80, R9 > 15				2					
Flood (°)		3000	Ra > 80, R9 > 15				2					
Spot (°)		3000	Ra > 80, R9 > 15				2					
Wide Flood (°)		3000	Ra > 80, R9 > 15				2					
Flood (°)		4000	Ra > 80, R9 > 15				2					
Spot (°)		4000	Ra > 80, R9 > 15				2					
Wide Flood (°)		4000	Ra > 80, R9 > 15				2					

Drivers

Clear Filters

Control	Input Power (W)	Input Voltage	Power Factor	THD (%)	Operation Ambient Temperature	InRush Current	Output Current	Output Power (Max-W)	Output Voltage (Range)	Dimming (Range)
---------	-----------------	---------------	--------------	---------	-------------------------------	----------------	----------------	----------------------	------------------------	-----------------

Transformer

Clear Filters

Control	Max Load (W)	Input Voltage	Power Factor	THD (%)	Operation Ambient Temperature	Output Current	Circuit Breaker	Min Load (W)
NON	20							
NON	10							
NON	75							
ELV, NON	60		95					

Finishes

STANDARD FINISHES









































PREMIUM FINISHES



RAL COLORS



 RAL 2002 (ral-2002)	 RAL 2001 (ral-2001)	 RAL 2000 (ral-2000)	 RAL 1037 (ral-1037)
 RAL 1034 (ral-1034)	 RAL 1033 (ral-1033)	 RAL 1032 (ral-1032)	 RAL 1028 (ral-1028)
 RAL 1027 (ral-1027)	 RAL 1024 (ral-1024)	 RAL 1023 (ral-1023)	 RAL 1021 (ral-1021)
 RAL 1020 (ral-1020)	 RAL 1019 (ral-1019)	 RAL 1017 (ral-1017)	 RAL 1016 (ral-1016)
 RAL 1015 (ral-1015)	 RAL 1014 (ral-1014)	 RAL 1013 (ral-1013)	 RAL 1012 (ral-1012)
 RAL 1011 (ral-1011)	 RAL 1007 (ral-1007)	 RAL 1006 (ral-1006)	 RAL 1005 (ral-1005)
 RAL 1004 (ral-1004)	 RAL 1002 (ral-1002)	 RAL 1001 (ral-1001)	 RAL 1000 (ral-1000)
 RAL 9018 (ral-9018)	 RAL 9010 (ral-9010)	 RAL 8003 (ral-8003)	 RAL 7002 (ral-7002)
 RAL 6002 (ral-6002)	 RAL 5005 (ral-5005)	 RAL 4001 (ral-4001)	 RAL 3002 (ral-3002)
 RAL 1018 (ral-1018)	 RAL 2008 (ral-2008)		

Mountings

Mountings With A Power Supply

This document contains proprietary information of B-K Lighting, inc. and its receipt or possession does not convey any rights to reproduce, disclose its contents, or to manufacture, use or sell anything it may describe.

Technical information is subject to change at the discretion of B-K Lighting Inc. For the most current technical data, please refer to bklighting.com