

ARTI STAR - Floodlight - Line Voltage Driver - LED COB - Stainless Steel - Pipe PI1 - 18" Junction Box - Cap D - Height: 20"



Technical

Delivered Lumens:	-
Control:	Non Dimming, ELV Dimming (For use with Electronic Low Voltage Dimmer), INC Dimming (For use with Incandescent Dimmer), 0-10V
Lens:	Clear (Standard), Soft Focus, Rectilinear
Shielding:	Not included (Standard), Honeycomb Baffle
Wiring length:	Standard
Input voltage:	120V, 120-277V

Light Source

LIGHT SOURCE ▾ OPTIC ▾ CCT CRI ▾ INPUT POWER (W) ▾

Clear Filters

Light Source	Optic	CCT (K)	CRI	Input Power (W)	Delivered Lumens (Lm)	CBCP	MacAdam Ellipses (SDCM)	Operating Current (mA)	L70 (Hours)	L90B10 (Hours)	IES File	Diagram CONE
	Flood (°)	2700	Ra > 80, R9 > 15				2					
	Spot (°)	2700	Ra > 80, R9 > 15				2					
	Wide Flood (°)	2700	Ra > 80, R9 > 15				2					
	Flood (°)	3000	Ra > 80, R9 > 15				2					
	Spot (°)	3000	Ra > 80, R9 > 15				2					
	Wide Flood (°)	3000	Ra > 80, R9 > 15				2					
	Flood (°)	4000	Ra > 80, R9 > 15				2					
	Spot (°)	4000	Ra > 80, R9 > 15				2					
	Wide Flood (°)	4000	Ra > 80, R9 > 15				2					

Drivers

CONTROL ▾ INPUT POWER (W) ▾

Clear Filters

Control	Input Power (W)	Input Voltage	Power Factor	THD (%)	Operation Ambient Temperature	InRush Current	Output Current	Output Power (Max-W)	Output Voltage (Range)	Dimming (Range)

Transformer

CONTROL ▾ MAX LOAD (W) ▾

Clear Filters

Control	Max Load (W)	Input Voltage	Power Factor	THD (%)	Operation Ambient Temperature	Output Current	Circuit Breaker	Min Load (W)
NON	75		95		1000		1000	1000
NON	20							
NON	10							
ELV, NON	60		95					

Finishes

STAINLESS STEEL FINISHES



Polished (Stainless Steel) (pss)



Machined (Stainless Steel) (mas)

Options

Accessory

Mountings

Mountings With A Power Supply