Project Date Type

ARTI STAR - Tree Mount - Line Voltage Driver - LED COB - Aluminum - Cap A - 6 Fixtures @ 60° - Strap: 31" Min. To 38" Max. Tree Diameter

INPUT POWER (W) -

Operation Ambient

Temperature

CBCP

MacAdam

Ellipses (SDCM)

InRush

Current

Operating

Output

Current

Current (mA)

L70

Output Power

(Max-W)

(Hours)

L90B10

(Hours)

Output Voltage

(Range)

Output Current Circuit Breaker

Diagram

CONE

Dimming

Min Load (W)

Updated 05/30/2024

(Range)

IES

File



120V, 120-277V

CCT CRI -

Delivered

THD

(%)

95

Lumens (Lm)



Technical

Delivered Lumens:

Light Source

Input voltage:

OPTIC -

LIGHT SOURCE -**Clear Filters**

Light Source

Input Optic CRI Power (W)

Drivers

INPUT POWER (W) -

MAX LOAD (W) -

Clear Filters

CONTROL -

Input Power Input **Power Control** (W) Voltage **Factor**

CONTROL -

Clear Filters

NON

Transformer

Input Voltage Power Factor THD (%) Operation Ambient Temperature **Control** Max Load (W) NON 20 NON 10

ELV, NON 60 **Finishes**

75

Options

Mountings

Mountings With A Power Supply

Accesory

This document contains proprietary information of B-K Lighting, inc. and its receipt or possession does not convey any rights to reproduce, disclose its contents, or to manufacture, use or sell anything it may describe.

Copyright © B-K Lighting, Inc. | 40429 Brickyard Drive Madera, CA 93636 | MADE IN USA | +1 (559) 438-5800 | info@bklighting.com | bklighting.com

Technical information is subject to change at the discretion of B-K Lighting Inc. For the most current technical data, please refer to bklighting.com