Project Date Type ARTI STAR - Tree Mount - Low Voltage Driver - LED High-Power - Aluminum - Cap F - 2 Fixtures @ 180° - Strap: 21" Min. To 27" Max. Tree Diameter



120V, 120-277V



Light Source

Technical

Delivered Lumens:

Input voltage:

LIGHT SOURCE -OPTIC -

Clear Filters

Input Light Optic CRI Power Source

(W)

Drivers

CONTROL -

Transformer

CONTROL -

Clear Filters

INPUT POWER (W) -

Voltage

MAX LOAD (W) -

Power

Factor

THD

(%)

95

CCT CRI -

Delivered

Lumens (Lm)

INPUT POWER (W) -

Operation Ambient

Input Voltage Power Factor THD (%) Operation Ambient Temperature

Copyright © B-K Lighting, Inc. | 40429 Brickyard Drive Madera, CA 93636 | MADE IN USA | +1 (559) 438-5800 | info@bklighting.com | bklighting.com

Technical information is subject to change at the discretion of B-K Lighting Inc. For the most current technical data, please refer to bklighting.com

This document contains proprietary information of B-K Lighting, inc. and its receipt or possession does not convey any rights to reproduce, disclose its contents, or to

Temperature

CBCP

MacAdam

Ellipses (SDCM)

InRush

Current

Operating

Output

Current

Current (mA)

L70

Output Power

(Max-W)

(Hours)

L90B10

(Hours)

Output Voltage

(Range)

Output Current Circuit Breaker

Diagram

CONE

Dimming

Min Load (W)

Updated 05/30/2024

(Range)

IES

File

Control (W)

Input Power Input

NON NON

Control

Clear Filters

NON 75 ELV, NON 60

Max Load (W)

20

10

Finishes

Options

Accesory

Mountings With A Power Supply

manufacture, use or sell anything it may describe.

Mountings