**Project** Type Date

ARTI STAR - Wall Mount - Remote Driver - LED COB

- Aluminum - Surface Mount - Cap E - Height: 3"

INPUT POWER (W) -

**Operation Ambient** 

Input Voltage Power Factor THD (%) Operation Ambient Temperature

**Temperature** 

**CBCP** 

MacAdam

Ellipses (SDCM)

InRush

Current

Operating

Output

**Current** 

Current (mA)

L70

**Output Power** 

(Max-W)

(Hours)

L90B10

(Hours)

**Output Voltage** 

(Range)

Output Current Circuit Breaker

Diagram

CONE

Dimming

Min Load (W)

Updated 05/30/2024

(Range)

**IES** 

File

120V, 120-277V

CCT CRI -

Power

(W)

CRI

**Delivered** 

**THD** 

(%)

95

Lumens (Lm)



**Light Source** 

Input voltage:

**Technical** 

**Delivered Lumens:** 

OPTIC -LIGHT SOURCE -

**Clear Filters** 

Input Light

Optic

Source

**Drivers** INPUT POWER (W) -

CONTROL -**Clear Filters** Input Power Input **Power Control** 

(W) Voltage **Factor** 

MAX LOAD (W) -

CONTROL -**Clear Filters** 

**Control** 

NON

Transformer

NON 10 NON 75 ELV, NON 60

20

Max Load (W)

**Finishes** 

Accesory

Mountings

**Options** 

Copyright © B-K Lighting, Inc. | 40429 Brickyard Drive Madera, CA 93636 | MADE IN USA | +1 (559) 438-5800 | info@bklighting.com | bklighting.com

manufacture, use or sell anything it may describe.

Mountings With A Power Supply

This document contains proprietary information of B-K Lighting, inc. and its receipt or possession does not convey any rights to reproduce, disclose its contents, or to

Technical information is subject to change at the discretion of B-K Lighting Inc. For the most current technical data, please refer to bklighting.com