Project Type Date

ARTI STAR - Wall Mount - Remote Driver - LED COB - Stainless Steel - Canopy BC6 - Cap D - Height: 6"





Input voltage:

Technical

Delivered Lumens:

Light Source

Input CCT CRI Power

120V, 120-277V

Light Optic Source

Clear Filters

Drivers

Clear Filters

Control

(W)

Transformer

Clear Filters

Control

NON

NON

NON

ELV, NON

Finishes

Voltage

Input Power Input

Max Load (W)

75

20

10

60

Power

Factor

Input Voltage

(W)

THD (%) **Temperature**

Power Factor

95

95

Delivered

Lumens (Lm)

Operation Ambient

THD (%)

1000

This document contains proprietary information of B-K Lighting, inc. and its receipt or possession does not convey any rights to reproduce, disclose its contents, or to

Technical information is subject to change at the discretion of B-K Lighting Inc. For the most current technical data, please refer to bklighting.com

CBCP

Operation Ambient Temperature

InRush

Current

MacAdam

Ellipses (SDCM)

Output

Current

Operating

Current (mA)

L70

Output Power

(Max-W)

(Hours)

L90B10

(Hours)

Output Voltage

(Range)

Output Current

Circuit Breaker 1000

Updated 06/04/2024

Diagram

CONE

Dimming

Min Load (W)

1000

(Range)

IES

File

STAINLESS STEEL FINISHES Polished Machined (Stainless (Stainless

Steel)

(mas)

Options

Steel) (pos)

Accesory Mountings

Copyright © B-K Lighting, Inc. | 40429 Brickyard Drive, Madera, CA 93636 | MADE IN USA | +1 (559) 438-5800 | info@bklighting.com | bklighting.com

Mountings With A Power Supply

manufacture, use or sell anything it may describe.