**Project** Date Type

CAMINO STAR - Bollard - Line Voltage Via Transformer - LED High-Power - Aluminum -Anchor Base - Style E - Height: 24"

INPUT POWER (W) -

**Operation Ambient** 

**Temperature** 

**CBCP** 

MacAdam

Ellipses (SDCM)

InRush

Current

Operating

Output

Current

Current (mA)

L70

**Output Power** 

**Output Current** 

(Max-W)

(Hours)

L90B10

(Hours)

**Output Voltage** 

**Circuit Breaker** 

(Range)

Diagram

CONE

Dimming

Min Load (W)

Updated 05/31/2024

(Range)

**IES** 

File



120V, 120-277V



**Light Source** 

**Clear Filters** 

**Technical** 

**Delivered Lumens:** 

Input voltage:

LIGHT SOURCE -OPTIC -

Input Light Optic CRI Power Source (W)

**Drivers** 

CCT CRI 🔻

**Delivered** 

THD

(%)

**Power Factor** 

Lumens (Lm)

**Clear Filters** 

(W)

Transformer

20

10

**Control** 

INPUT POWER (W) -CONTROL -

**Power** 

**Factor** 

CONTROL -

NON

NON

**Clear Filters** Control Max Load (W)

Input Power Input

Voltage

MAX LOAD (W) -

Input Voltage

**Finishes** 

THD (%) Operation Ambient Temperature

**Options** 

Accesory

Mountings With A Power Supply

manufacture, use or sell anything it may describe.

Mountings

Copyright © B-K Lighting, Inc. | 40429 Brickyard Drive Madera, CA 93636 | MADE IN USA | +1 (559) 438-5800 | info@bklighting.com | bklighting.com

Technical information is subject to change at the discretion of B-K Lighting Inc. For the most current technical data, please refer to bklighting.com

This document contains proprietary information of B-K Lighting, inc. and its receipt or possession does not convey any rights to reproduce, disclose its contents, or to