Project Date Type

DENALI - Tree Mount - Line Voltage Driver - LED Color Tuning - Aluminum - Cap B - 4 Fixtures @ 90° - Strap: 26" Min. To 32" Max. Tree Diameter



2700, 3000, 4000, 3500

120-277V

Ra > 80, R9 > 15, Ra > 90, R9 > 50, Ra > 80, R9 > 15

INPUT POWER (W) -

Operation Ambient

Temperature

CBCP

MacAdam

Ellipses (SDCM)

InRush

THD (%) Operation Ambient Temperature

Current

Operating

Output

Current

Current (mA)

L70

Output Power

Output Current

(Max-W)

(Hours)

L90B10

(Hours)

Output Voltage

Circuit Breaker

(Range)

IES

File

Diagram

CONE

Dimming

Min Load (W)

Updated 05/30/2024

(Range)

Delivered

THD

(%)

Power Factor

Lumens (Lm)



CCT(K):

CRI:

Technical

Delivered Lumens:

Input voltage:

Light Source CCT CRI -

LIGHT SOURCE -OPTIC -**Clear Filters**

Input Light CCT CRI Power Source (W)

Drivers

CONTROL -

Clear Filters

Control Max Load (W)

INPUT POWER (W) -

Input Voltage

Clear Filters Input Power Input **Power Control** Voltage **Factor**

Transformer MAX LOAD (W) -CONTROL -

Finishes

Options

Accesory

Mountings

Mountings With A Power Supply

Technical information is subject to change at the discretion of B-K Lighting Inc. For the most current technical data, please refer to bklighting.com

manufacture, use or sell anything it may describe.

Copyright © B-K Lighting, Inc. | 40429 Brickyard Drive Madera, CA 93636 | MADE IN USA | +1 (559) 438-5800 | info@bklighting.com | bklighting.com

This document contains proprietary information of B-K Lighting, inc. and its receipt or possession does not convey any rights to reproduce, disclose its contents, or to