**Project** Date Type DENALI - Wall Mount - Remote Driver - LED COB -Aluminum - Canopy BC14 - Cap C - Style B - 2 Fixtures - Stem Length: 30"



120V, 120-277V

CCT CRI 🔻

Delivered

THD

(%)

**Power Factor** 

Lumens (Lm)

INPUT POWER (W) -

**Operation Ambient** 

**Temperature** 

**CBCP** 

MacAdam

Ellipses (SDCM)

InRush

THD (%) Operation Ambient Temperature

Current

Operating

Output

Current

Current (mA)

L70

**Output Power** 

**Output Current** 

(Max-W)

(Hours)

L90B10

(Hours)

**Output Voltage** 

**Circuit Breaker** 

(Range)

**IES** 

File

Diagram

CONE

Dimming

(Range)

Min Load (W)

Updated 05/30/2024



Light Source

**Technical** 

**Delivered Lumens:** 

Input voltage:

OPTIC -LIGHT SOURCE -**Clear Filters** 

(°)

Input Light CCT Optic CRI Power Source (W)

**Drivers** 

CONTROL -**Clear Filters** 

**Control** 

Input Power Input (W) Voltage **Factor** 

MAX LOAD (W) -

Input Voltage

INPUT POWER (W) -

Power

Transformer CONTROL ▼

**Clear Filters** 

**Finishes** 

Control Max Load (W)

**Options** 

Mountings With A Power Supply

Mountings

Accesory

manufacture, use or sell anything it may describe. Technical information is subject to change at the discretion of B-K Lighting Inc. For the most current technical data, please refer to bklighting.com

Copyright © B-K Lighting, Inc. | 40429 Brickyard Drive Madera, CA 93636 | MADE IN USA | +1 (559) 438-5800 | info@bklighting.com | bklighting.com

This document contains proprietary information of B-K Lighting, inc. and its receipt or possession does not convey any rights to reproduce, disclose its contents, or to