Project Date Type GLOW STAR - Bollard - Line Voltage Via Transformer - LED High-Power - Aluminum - Pipe Pl1 - 18" Junction Box - Style P1 - Height: 18"



120V, 120-277V

CCT CRI -

Delivered

THD

(%)

Lumens (Lm)

INPUT POWER (W) -

Operation Ambient

Power Factor THD (%) Operation Ambient Temperature

Temperature

CBCP

MacAdam

Ellipses (SDCM)

InRush

Current



Light Source

Technical

Delivered Lumens:

Input voltage:

LIGHT SOURCE -OPTIC -

Light Source

Clear Filters

Input Optic CRI Power

(W)

Drivers

CONTROL -

Clear Filters Input Power Input **Power Control** (W) Voltage **Factor**

INPUT POWER (W) -

Transformer

Control

NON

NON

NON

MAX LOAD (W) -CONTROL -**Clear Filters**

Max Load (W)

20 10 ELV, NON 60

Input Voltage

95

95

Finishes

75

Options

Accesory

Mountings

Mountings With A Power Supply

manufacture, use or sell anything it may describe.

Copyright © B-K Lighting, Inc. | 40429 Brickyard Drive Madera, CA 93636 | MADE IN USA | +1 (559) 438-5800 | info@bklighting.com | bklighting.com

This document contains proprietary information of B-K Lighting, inc. and its receipt or possession does not convey any rights to reproduce, disclose its contents, or to

Technical information is subject to change at the discretion of B-K Lighting Inc. For the most current technical data, please refer to bklighting.com

Operating

Current (mA)

L70

(Hours)

Dimming **Output Power Output Voltage** Output Current (Max-W) (Range) (Range)

L90B10

(Hours)

Diagram

CONE

IES

File

Output Current Circuit Breaker Min Load (W)

Updated 05/30/2024