Date Project Type

HUME - Light Pole - Line Voltage Driver - LED COB - Aluminum - Round - Side Knuckle - Round Straight Aluminum Pole 4" - Cap C - 3 Fixtures -Spiral - Height: 12"





Diagram

CONE

Dimming (Range)

Min Load (W)

Updated 05/31/2024

Output Current Circuit Breaker

Technical								
Delivered Lumens: Input voltage:	- 120V, 120-277V							
Light Source								
LIGHT SOURCE ▼ Clear Filters	OPTIC V	CRI - INPUT I	POWER (W) 🔻					
Light Optic Source	CCT CRI Power (W)	Delivered Lumens (Lm)	(:H(:D	acAdam lipses (SDCM)	Operating Current (mA)	L70 (Hours)	L90B10 (Hours)	IES File
Drivers								
CONTROL ~	INPUT POWER (W)							
Clear Filters								
Control Input Powe (W) Transformer	r Input Power Voltage Factor	THD Operati (%) Tempera	on Ambient ature	InRush Current	Output Current	Output Power (Max-W)	Output Vo (Range)	oltage
	MAX LOAD (W) -							

Control Max Load (W) Input Voltage Power Factor THD (%) Operation Ambient Temperature

Options Accesory

Mountings With A Power Supply

Clear Filters

Finishes

Mountings

manufacture, use or sell anything it may describe.

Copyright © B-K Lighting, Inc. | 40429 Brickyard Drive Madera, CA 93636 | MADE IN USA | +1 (559) 438-5800 | info@bklighting.com | bklighting.com

Technical information is subject to change at the discretion of B-K Lighting Inc. For the most current technical data, please refer to bklighting.com

This document contains proprietary information of B-K Lighting, inc. and its receipt or possession does not convey any rights to reproduce, disclose its contents, or to