Project Date Type MINI MICRO - Ceiling Mount - Low Voltage Driver - LED High-Power - Stainless Steel - Stem Mount -Cap E - Stem Length: 18"



120V, 120-277V

CCT CRI -

Delivered

THD

(%)

Power Factor

Lumens (Lm)

INPUT POWER (W) -

Operation Ambient

Temperature

CBCP

MacAdam

Ellipses (SDCM)

InRush

THD (%) Operation Ambient Temperature

Current

Operating

Output

Current

Current (mA)

L70

Output Power

Output Current

(Max-W)

(Hours)

L90B10

(Hours)

Output Voltage

Circuit Breaker

(Range)

IES

File

Diagram

CONE

Dimming

Min Load (W)

Updated 06/02/2024

(Range)



| Light | Source |
|-------|--------|
| | |

Technical

Delivered Lumens:

Input voltage:

LIGHT SOURCE -OPTIC -**Clear Filters**

Light

Input Optic **CRI** Power Source

(W)

Drivers

CONTROL -

Clear Filters Input Power Input **Power** Control (W) Voltage **Factor**

INPUT POWER (W) -

MAX LOAD (W) -

CONTROL ▼

Clear Filters

NON

Finishes

(Stainless

Steel)

(pos)

Transformer

Max Load (W) Control Input Voltage NON 20

10

Polished Machined

STAINLESS STEEL FINISHES

(Stainless Steel)

(mas)

Options

Accesory

Mountings

Mountings With A Power Supply

manufacture, use or sell anything it may describe.

Copyright © B-K Lighting, Inc. | 40429 Brickyard Drive Madera, CA 93636 | MADE IN USA | +1 (559) 438-5800 | info@bklighting.com | bklighting.com

Technical information is subject to change at the discretion of B-K Lighting Inc. For the most current technical data, please refer to bklighting.com

This document contains proprietary information of B-K Lighting, inc. and its receipt or possession does not convey any rights to reproduce, disclose its contents, or to