

MICRO NITE - Ceiling Mount - Low Voltage Driver - Lamp MR11 - Brass - Pendant Mount - Cap C - Fixed - Single



Technical

Delivered Lumens: -

Light Source

Clear Filters

| Light Source | Optic | CCT (K) | CRI | Input Power (W) | Delivered Lumens (Lm) | CBCP | MacAdam Ellipses (SDCM) | Operating Current (mA) | L70 (Hours) | L90B10 (Hours) | IES File | Diagram CONE |
|--------------|-------|---------|-----|-----------------|-----------------------|------|-------------------------|------------------------|-------------|----------------|----------|--------------|
|--------------|-------|---------|-----|-----------------|-----------------------|------|-------------------------|------------------------|-------------|----------------|----------|--------------|

Drivers

Clear Filters

| Control | Input Power (W) | Input Voltage | Power Factor | THD (%) | Operation Ambient Temperature | InRush Current | Output Current | Output Power (Max-W) | Output Voltage (Range) | Dimming (Range) |
|---------|-----------------|---------------|--------------|---------|-------------------------------|----------------|----------------|----------------------|------------------------|-----------------|
|---------|-----------------|---------------|--------------|---------|-------------------------------|----------------|----------------|----------------------|------------------------|-----------------|

Transformer

Clear Filters

| Control | Max Load (W) | Input Voltage | Power Factor | THD (%) | Operation Ambient Temperature | Output Current | Circuit Breaker | Min Load (W) |
|---------|--------------|---------------|--------------|---------|-------------------------------|----------------|-----------------|--------------|
|---------|--------------|---------------|--------------|---------|-------------------------------|----------------|-----------------|--------------|

NON 20

NON 10

Finishes

Options

Accessory

Mountings

Mountings With A Power Supply