

MICRO NITE - Wall Mount - Low Voltage Driver - LED High-Power - Aluminum - Surface Mount - Cap D - Style B - Single - Stem Length: 18"



Technical

Delivered Lumens: -
 Input voltage: 120V, 120-277V

Light Source

Clear Filters

| Light Source | Optic | CCT (K) | CRI | Input Power (W) | Delivered Lumens (Lm) | CBCP | MacAdam Ellipse (SDCM) | Operating Current (mA) | L70 (Hours) | L90B10 (Hours) | IES File | Diagram CONE |
|--------------|-------|---------|-----|-----------------|-----------------------|------|------------------------|------------------------|-------------|----------------|----------|--------------|
|--------------|-------|---------|-----|-----------------|-----------------------|------|------------------------|------------------------|-------------|----------------|----------|--------------|

Drivers

Clear Filters

| Control | Input Power (W) | Input Voltage | Power Factor | THD (%) | Operation Ambient Temperature | InRush Current | Output Current | Output Power (Max-W) | Output Voltage (Range) | Dimming (Range) |
|---------|-----------------|---------------|--------------|---------|-------------------------------|----------------|----------------|----------------------|------------------------|-----------------|
|---------|-----------------|---------------|--------------|---------|-------------------------------|----------------|----------------|----------------------|------------------------|-----------------|

Transformer

Clear Filters

| Control | Max Load (W) | Input Voltage | Power Factor | THD (%) | Operation Ambient Temperature | Output Current | Circuit Breaker | Min Load (W) |
|---------|--------------|---------------|--------------|---------|-------------------------------|----------------|-----------------|--------------|
|---------|--------------|---------------|--------------|---------|-------------------------------|----------------|-----------------|--------------|

Finishes

STANDARD FINISHES





















PREMIUM FINISHES



RAL COLORS



| | | | |
|---|--|--|--|
|  RAL 1011 (ral-1011) |  RAL 1007 (ral-1007) |  RAL 1006 (ral-1006) |  RAL 1005 (ral-1005) |
|  RAL 1004 (ral-1004) |  RAL 1002 (ral-1002) |  RAL 1001 (ral-1001) |  RAL 1000 (ral-1000) |
|  RAL 9018 (ral-9018) |  RAL 9010 (ral-9010) |  RAL 8003 (ral-8003) |  RAL 7002 (ral-7002) |
|  RAL 6002 (ral-6002) |  RAL 5005 (ral-5005) |  RAL 4001 (ral-4001) |  RAL 3002 (ral-3002) |
|  RAL 1018 (ral-1018) |  RAL 2008 (ral-2008) | | |

Mountings

Mountings With A Power Supply

This document contains proprietary information of B-K Lighting, inc. and its receipt or possession does not convey any rights to reproduce, disclose its contents, or to manufacture, use or sell anything it may describe.

Technical information is subject to change at the discretion of B-K Lighting Inc. For the most current technical data, please refer to bklighting.com