

MICRO NITE - Wall Mount - Low Voltage Driver - LED High-Power - Aluminum - Surface Mount - Cap E - Style G - 2 Fixtures - Stem Length: 48"



Technical

Delivered Lumens:	-
Input voltage:	120V, 120-277V

Light Source

LIGHT SOURCE ▾	OPTIC ▾	CCT CRI ▾	INPUT POWER (W) ▾
-----------------------	----------------	------------------	--------------------------

Clear Filters

Light Source	Optic	CCT (K)	CRI	Input Power (W)	Delivered Lumens (Lm)	CBCP	MacAdam Ellipses (SDCM)	Operating Current (mA)	L70 (Hours)	L90B10 (Hours)	IES File	Diagram CONE
--------------	-------	---------	-----	-----------------	-----------------------	------	-------------------------	------------------------	-------------	----------------	----------	--------------

Drivers

CONTROL ▾	INPUT POWER (W) ▾
------------------	--------------------------

Clear Filters

Control	Input Power (W)	Input Voltage	Power Factor	THD (%)	Operation Ambient Temperature	InRush Current	Output Current	Output Power (Max-W)	Output Voltage (Range)	Dimming (Range)
---------	-----------------	---------------	--------------	---------	-------------------------------	----------------	----------------	----------------------	------------------------	-----------------

Transformer

CONTROL ▾	MAX LOAD (W) ▾
------------------	-----------------------

Clear Filters

Control	Max Load (W)	Input Voltage	Power Factor	THD (%)	Operation Ambient Temperature	Output Current	Circuit Breaker	Min Load (W)
NON	20							
NON	10							

Finishes

Options

Accessory

Mountings

Mountings With A Power Supply