NITE STAR - Bollard - Line Voltage Via Transformer - LED High-Power - Aluminum - Round - Power Pipe PP1 - 18" Junction Box - Cap D - Style L -Single - Height: 30"





Technical

 Delivered Lumens:

 Input voltage:
 120V, 120-277V

Light Source

]				ers
BCP MacAdam	CBCP	Input Power Delivered CBCP MacAdam (W) Lumens (Lm) CBCP Ellipses (SDCN	CRI Power Lumens (Lm) CBCP Filinges (SDC)	(K) CRI Power Lumens (Lm) CBCP Ellipses (SDC)	Optic (K) CRI Power Delivered CBCP Filipses (SDC)

Drivers

CONT		IPUT POWE	R (W) 👻							
Clear Filt	ters									
Control	Input Power (W)	Input Voltage	Power Factor	THD (%)	Operation Ambient Temperature	InRush Current	Output Current	Output Power (Max-W)	Output Voltage (Range)	Dimming (Range)

Transformer



Clear Filters

Con	trol	Max Load (W)	Input Voltage	Power Factor	THD (%)	Operation Ambient Temperature	Output Current	Circuit Breaker	Min Load (W)
NON		20							
NON		10							
ELV,	NON	60		95					
NON		75		95					

Finishes

Options

Accesory

Mountings

Mountings With A Power Supply

Copyright © B-K Lighting, Inc. | 40429 Brickyard Drive Madera, CA 93636 | MADE IN USA | +1 (559) 438-5800 | info@bklighting.com | bklighting.com

This document contains proprietary information of B-K Lighting, inc. and its receipt or possession does not convey any rights to reproduce, disclose its contents, or to manufacture, use or sell anything it may describe.

Technical information is subject to change at the discretion of B-K Lighting Inc. For the most current technical data, please refer to bklighting.com

Updated 05/30/2024