Project Date Type

NITE STAR - Ceiling Mount - Low Voltage Driver - LED High-Power - Brass - Round - Stem Mount -Cap F - Stem Length: 36"

INPUT POWER (W) -

Operation Ambient

Power Factor THD (%) Operation Ambient Temperature

Temperature

CBCP

MacAdam

Ellipses (SDCM)

InRush

Current

Operating

Output

Current

Current (mA)

L70

Output Power

(Max-W)

(Hours)

L90B10

(Hours)

Output Voltage

(Range)

Output Current Circuit Breaker

IES

File

Diagram

CONE

Dimming

Min Load (W)

Updated 05/30/2024

(Range)



120V, 120-277V

CCT CRI -

Delivered

THD

(%)

Factor

Input Voltage

95

95

Lumens (Lm)



Light Source

Technical

Delivered Lumens:

Input voltage:

LIGHT SOURCE -OPTIC -

Clear Filters

Source

Input Light Optic CRI Power (W)

Drivers

INPUT POWER (W) -

Voltage

CONTROL -

(W)

Clear Filters Input Power Input **Power Control**

Transformer

Control

NON

NON

MAX LOAD (W) -CONTROL -**Clear Filters**

Max Load (W)

ELV, NON 60 NON

75

20

10

Finishes

Options

Accesory

Mountings

Mountings With A Power Supply

manufacture, use or sell anything it may describe.

Copyright © B-K Lighting, Inc. | 40429 Brickyard Drive Madera, CA 93636 | MADE IN USA | +1 (559) 438-5800 | info@bklighting.com | bklighting.com

Technical information is subject to change at the discretion of B-K Lighting Inc. For the most current technical data, please refer to bklighting.com

This document contains proprietary information of B-K Lighting, inc. and its receipt or possession does not convey any rights to reproduce, disclose its contents, or to