

# NITE STAR - Tree Mount - Low Voltage Driver - Lamp MR16 Gu5.3 - Aluminum - Round - Cap B - 3 Fixtures @ 120° - Strap: 16" Min. To 22" Max. Tree Diameter



## Technical

Delivered Lumens: -

## Light Source

Clear Filters

Light Source	Optic	CCT (K)	CRI	Input Power (W)	Delivered Lumens (Lm)	CBCP	MacAdam Ellipses (SDCM)	Operating Current (mA)	L70 (Hours)	L90B10 (Hours)	IES File	Diagram CONE
--------------	-------	---------	-----	-----------------	-----------------------	------	-------------------------	------------------------	-------------	----------------	----------	--------------

## Drivers

Clear Filters

Control	Input Power (W)	Input Voltage	Power Factor	THD (%)	Operation Ambient Temperature	InRush Current	Output Current	Output Power (Max-W)	Output Voltage (Range)	Dimming (Range)
---------	-----------------	---------------	--------------	---------	-------------------------------	----------------	----------------	----------------------	------------------------	-----------------

## Transformer

Clear Filters

Control	Max Load (W)	Input Voltage	Power Factor	THD (%)	Operation Ambient Temperature	Output Current	Circuit Breaker	Min Load (W)
NON	20							
NON	10							
ELV, NON	60		95		1000		1000	1000
NON	75		95		1000		1000	1000

## Finishes

### STANDARD FINISHES






### PREMIUM FINISHES



### RAL COLORS



 RAL 1004 (ral-1004)	 RAL 1002 (ral-1002)	 RAL 1001 (ral-1001)	 RAL 1000 (ral-1000)
 RAL 9018 (ral-9018)	 RAL 9010 (ral-9010)	 RAL 8003 (ral-8003)	 RAL 7002 (ral-7002)
 RAL 6002 (ral-6002)	 RAL 5005 (ral-5005)	 RAL 4001 (ral-4001)	 RAL 3002 (ral-3002)
 RAL 1018 (ral-1018)	 RAL 2008 (ral-2008)		

## Mountings

### Mountings With A Power Supply