


NITE STAR - Wall Mount - Line Voltage Via Transformer - Lamp MR16 Gu5.3 - Aluminum - Round - Universal Power Module PM1 - Cap F - Style C - Single - Stem Length: 18"



Technical

Delivered Lumens: -

Light Source

Clear Filters

| Light Source | Optic | CCT (K) | CRI | Input Power (W) | Delivered Lumens (Lm) | CBCP | MacAdam Ellipses (SDCM) | Operating Current (mA) | L70 (Hours) | L90B10 (Hours) | IES File | Diagram CONE |
|--------------|-------|---------|-----|-----------------|-----------------------|------|-------------------------|------------------------|-------------|----------------|----------|--------------|
|--------------|-------|---------|-----|-----------------|-----------------------|------|-------------------------|------------------------|-------------|----------------|----------|--------------|

Drivers

Clear Filters

| Control | Input Power (W) | Input Voltage | Power Factor | THD (%) | Operation Ambient Temperature | InRush Current | Output Current | Output Power (Max-W) | Output Voltage (Range) | Dimming (Range) |
|---------|-----------------|---------------|--------------|---------|-------------------------------|----------------|----------------|----------------------|------------------------|-----------------|
|---------|-----------------|---------------|--------------|---------|-------------------------------|----------------|----------------|----------------------|------------------------|-----------------|

Transformer

Clear Filters

| Control | Max Load (W) | Input Voltage | Power Factor | THD (%) | Operation Ambient Temperature | Output Current | Circuit Breaker | Min Load (W) |
|----------|--------------|---------------|--------------|---------|-------------------------------|----------------|-----------------|--------------|
| NON | 20 | | | | | | | |
| NON | 10 | | | | | | | |
| ELV, NON | 60 | | 95 | | | | | |
| NON | 75 | | 95 | | | | | |

Finishes

Options

Accessory

Mountings

Mountings With A Power Supply