

NITE STAR - Wall Mount - Line Voltage Via Transformer - LED High-Power - Aluminum - Round - Power Canopy PC1 - Cap E - Style F - Single -Stem Length: 18"





Туре

Technical

Date

 Delivered Lumens:

 Input voltage:
 120V, 120-277V

Light Source

LIGHT SC Clear Filter	DURCE -	OP		CCT CR		OWER (W)	•					
Light Source	Optic	ССТ (К)	CRI	Input Power (W)	Delivered Lumens (Lm)	CBCP	MacAdam Ellipses (SDCM)	Operating Current (mA)	L70 (Hours)	L90B10 (Hours)	IES File	Diagram CONE

Drivers

Clear Filters		
ControlInput PowerInputPowerTHDOperation AmbientInRu(W)VoltageFactor(%)TemperatureCurr	o Output Output Power	Output Voltage Dimr

Transformer



Clear Filters

Con	trol	Max Load (W)	Input Voltage	Power Factor	THD (%)	Operation Ambient Temperature	Output Current	Circuit Breaker	Min Load (W)
NON		20							
NON		10							
ELV,	NON	60		95					
NON		75		95					

Finishes

Options

Accesory

Mountings

Mountings With A Power Supply

Copyright © B-K Lighting, Inc. | 40429 Brickyard Drive Madera, CA 93636 | MADE IN USA | +1 (559) 438-5800 | info@bklighting.com | bklighting.com

This document contains proprietary information of B-K Lighting, inc. and its receipt or possession does not convey any rights to reproduce, disclose its contents, or to manufacture, use or sell anything it may describe.

Technical information is subject to change at the discretion of B-K Lighting Inc. For the most current technical data, please refer to bklighting.com

Updated 05/30/2024