Project Type Date

RIO - Light Pole - Line Voltage Driver - LED High-Power - Aluminum - Round - Round Straight Aluminum Pole 4" - Cap E - 3 Fixtures - Spiral -Height: 16"



Diagram

CONE

Dimming

Min Load (W)

(Range)

IES

File

Operating

Output

Current

Current (mA)

L70

Output Power

Output Current

(Max-W)

(Hours)

L90B10

(Hours)

Output Voltage

Circuit Breaker

(Range)

MacAdam

Ellipses (SDCM)

InRush

Current

THD (%) Operation Ambient Temperature

B-K LIGHTING		B-LIGHT
Technical		
Delivered Lumens: Input voltage:	- 120V, 120-277V	
Light Source		
LIGHT SOURCE Clear Filters	OPTIC ▼ CCT CRI ▼ INPUT POWER (W) ▼	

Input Light **Delivered** Power **CBCP** Optic CRI Lumens (Lm) Source (W)

Drivers INPUT POWER (W) -CONTROL -**Clear Filters**

Input Power THD **Operation Ambient** Input **Power Control** Voltage (%) (W) **Factor Temperature** Transformer

MAX LOAD (W) -

Input Voltage

Power Factor

Finishes

CONTROL -

Control Max Load (W)

Clear Filters

Options Accesory

Mountings

Mountings With A Power Supply

Copyright © B-K Lighting, Inc. | 40429 Brickyard Drive Madera, CA 93636 | MADE IN USA | +1 (559) 438-5800 | info@bklighting.com | bklighting.com

manufacture, use or sell anything it may describe.

This document contains proprietary information of B-K Lighting, inc. and its receipt or possession does not convey any rights to reproduce, disclose its contents, or to

Technical information is subject to change at the discretion of B-K Lighting Inc. For the most current technical data, please refer to bklighting.com

Updated 05/31/2024